

Specifications:	XA200.8	XA160.8	XA100.8	XA60.8	XA30.8
Class	A	A	A	A	A
Type	Mono	Mono	Mono	Mono	Stereo
Gain (dB)	26	26	26	26	26
Full Pwr @ 26 dB gain (V)	2.00	1.79	1.41	1.10	0.77
Low Frequency Response	1.5 Hz	1.5 Hz	1.5 Hz	1.5 Hz	1.5 Hz
High Frequency Response	100 KHz	100 KHz	100 KHz	100 KHz	100 KHz
Power Output /ch (8 ohm)	200	160	100	60	30
Power Output /ch (4 ohm)	400	320	200	120	60
Distortion, (1 KHz, full power)	1%	1%	1%	1%	1%
Maximum Output (Volts)	62	56	48	48	40
Maximum Output (Amps)	50	50	40	30	20
Input Impedance (SE & BAL Kohms)	50 /100	50/100	50 /100	50/100	50 /100
Damping Factor	200	200	200	150	150
Slew Rate (V/uS)	50	50	50	50	50
Output Noise (uV)	200	200	200	200	200
Input CMRR (dB)	-60	-60	-60	-60	-60
DC Offset (V)	0.05	0.05	0.05	0.05	0.05
Leaves Class A at pk Watts:	430	328	241	122	61
Current Draw @ Idle (Amps)	6.1	4.6	3.7	3.1	3.1
Power Consumption (Watts)	750	550	450	375	375
Temperature (deg C.)	53	53	53	53	53
Unit Dimension (W x D x H) (In.)	19 x 27.5 x 11	19 x 21.5 x 11	19 x 21.25 x 9	19 x 21.25 x 7.5	19 x 21.25 x 7.5
Unit Weight (LBS)					
Ship Box Dim (W x D x H)	33 x 24 x 16	27 x 24 x 16	27 x 24 x 15	27 x 25 x 14	27 x 25 x 14
Ship Weight (LBS)	177	141	117	107	106

Specifications:	X600.8	X350.8	X250.8	X260.8	X150.8
Class	AB	AB	AB	AB	AB
Type	Mono	Stereo	Stereo	Mono	Stereo
Gain (dB)	26	26	26	26	26
Full Pwr @ 26 dB gain (V)	3.46	2.65	2.24	2.2	1.73
Low Frequency Response	1.5 Hz	1.5 Hz	1.5 Hz	1.5Hz	1.5 Hz
High Frequency Response	100 KHz	100 KHz	100 KHz	100KHz	100 KHz
Power Output /ch (8 ohm)	600	350	250	260	150
Power Output /ch (4 ohm)	1200	700	500	520	300
Distortion, (1 KHz, full power)	1%	1%	1%	1%	1%
Maximum Output (Volts)	120	104	80	80	64
Maximum Output (Amps)	50	35	28	28	20
Input Impedance (SE & BAL Kohms)	50 /100	50/100	50 /100	50/100	50 /100
Damping Factor	200	150	150	150	150
Slew Rate (V/uS)	50	50	50	50	50
Output Noise (uV)	200	200	200	200	200
Input CMRR (dB)	-60	-60	-60	-60	-60
DC Offset (V)	0.05	0.05	0.05	0.05	0.05
Leaves Class A at pk Watts:	100	18	16	34	13
Current Draw @ Idle (Amps)	4.6	4.6	3.4	3.1	2.9
Power Consumption (Watts)	550	550	450	375	375
Temperature (deg C.)	53	53	53	53	53
Unit Dimension (W x D x H)	19 x 21.5 x 11	19 x 21.5 x 11	19 x 21.25 x 9	19 x 21.25 x 7.5	19 x 21.25 x 7.5
Unit Weight (LBS)					
Ship Box Dim (W x D x H)	27 x 24 x 16	27 x 24 x 16	27 x 24 x 15	27 x 25 x 14	27 x 25 x 14
Ship Weight (LBS)	141	145	118	105	105