

Specifications:	XA200.8	XA160.8	XA100.8	XA60.8	XA30.8
Class	A	A	A	A	A
Type	Mono	Mono	Mono	Mono	Stereo
Gain (dB)	26	26	26	26	26
Full Pwr @ 26 dB gain (V)	2.00	1.79	1.41	1.10	0.77
Low Frequency Response	1.5 Hz	1.5 Hz	1.5 Hz	1.5 Hz	1.5 Hz
High Frequency Response	100 KHz	100 KHz	100 KHz	100 KHz	100 KHz
Power Output /ch (8 ohm)	200	160	100	60	30
Input Impedance (SE & BAL Kohms)	50 /100	50/100	50 /100	50/100	50 /100
Damping Factor	200	200	200	150	150
Power Consumption @ Idle (Watts)	760	600	500	370	370
Unit Dimension (W x D x H) (In.)	19 x 27.5 x 11	19 x 21.5 x 11	19 x 21.25 x 9	19 x 21.25 x 7.5	19 x 21.25 x 7.5
Unit Weight (LBS)					

Specifications:	X600.8	X350.8	X250.8	X260.8	X150.8
Class	AB	AB	AB	AB	AB
Type	Mono	Stereo	Stereo	Mono	Stereo
Gain (dB)	26	26	26	26	26
Full Pwr @ 26 dB gain (V)	3.46	2.65	2.24	2.2	1.73
Low Frequency Response	1.5 Hz	1.5 Hz	1.5 Hz	1.5Hz	1.5 Hz
High Frequency Response	100 KHz	100 KHz	100 KHz	100KHz	100 KHz
Power Output /ch (8 ohm)	600	350	250	260	150
Input Impedance (SE & BAL Kohms)	50 /100	50/100	50 /100	50/100	50 /100
Damping Factor	200	150	150	150	150
Power Consumption @ idle (Watts)	600	600	500	370	370
Unit Dimension (W x D x H)	19 x 21.5 x 11	19 x 21.5 x 11	19 x 21.25 x 9	19 x 21.25 x 7.5	19 x 21.25 x 7.5
Unit Weight (LBS)					